

Stewart

Filmscreen Corporation®

P i c t u r e P e r f e c t



Stealth Trap Door ElectriScreen

Hidden from View

The Stealth Trap Door ElectriScreen utilizes a technologically advanced electric roll-up screen. The screen retracts into an obscure trap door that mounts flush with the ceiling surface and can be painted to blend perfectly, effectively hiding its existence.

Insist on the Best

Optimize your Stealth Trap Door ElectriScreen with a Stewart Academy Award® winning screen material, securely attached using our exclusive Tab-Guy tensioning system designed to ensure a smooth flat image and prevent curl up.

Motorized Roller System


Stewart's motorized roller system provides a quite, reliable screen operation that can be activated by a switch, infrared or remote control, or a projector screen trigger.

Trust Stewart

Stewart Filmscreen is synonymous with high quality materials, superior craftsmanship and long, trouble-free product life. Since every Stewart Filmscreen product is hand crafted, custom sizes and configurations can also be accommodated. Call Stewart Filmscreen today and we will build one for you.

Stealth Trap Door ElectriScreen Specifications

Dimensions represented in inches (") and millimeters (mm). Weights represented in pounds (lbs.) and kilograms (kg.)



Formats	Min-Max Height	Min-Max Width
Video Format	36"-72"	48"-96"
HDTV	40.5"-54"	72"-96"
Widescreen	39"-48"	72"-89"

(Size height and width depends on model chosen.
Custom sizes available with no extra charge.)

Case Material

Aluminum Extrusion

Specifications

Case Colors	White
Batten Colors	Black, White

Screen Materials

Front Projection	Gain	Viewing Angle
GrayHawk RS	.92	128°
StuDiotek / Ultramatte 130	1.3	160°
FireHawk	1.35	100°
Ultramatte 150	1.5	140°
Videomatte 200	1.8	120°
Ultramatte 200	2.0	120°

Perforation (Front Projection)

THX Certified MicroPerf	Optional
CinePerf	Optional

Rear Projection	Gain	Viewing Angle
Aeroview 100	1.0	180°
Filmscreen 100	1.0	100°-120°
Lumiflex 130	1.3	160°
Filmscreen 150	1.5	120°

Standard Features

Tab-Guy Tensioning System
Roller Tube System
Seamless Screen Materials
Motorized Trap Door

Screen Motor:	120 Volt = 38 rpm, 1 amp
	220 Volt = 32 rpm, 1 amp

Control Systems : Screen

High Voltage Wall Switch	Included
Low Voltage Control	Optional
Wireless Remote Control	Optional
Infrared Remote Control	Optional
Screen Trigger Interface	Optional
Video Interface Control	Optional

Mounting Hardware

Ceiling/Soffit Recessed	Included
Wall Mount/Brackets	Optional

For custom sizes and gains, please consult the Screen Assistant software or Stewart Sales desk.

Video Format (4:3 Aspect Ratio)

Model Number	Image Diagonal	Image Height	Image Width
SEL060V	60" (1524mm)	36 (914)	48 (1219)
SEL072V	72 (1829)	43 (1092)	57 (1448)
SEL084V	84 (2134)	50 (1270)	67 (1702)
SEL090V	90 (2286)	54 (1372)	72 (1829)
SEL100V	100 (2540)	60 (1524)	80 (2032)
SEL120V	120 (3048)	72 (1829)	96 (2438)

HDTV Format (16:9 Aspect Ratio)

Model Number	Image Diagonal	Image Height	Image Width
SEL082H	82 (2083)	40.5 (1029)	72 (1829)
SEL092H	92 (2337)	45 (1143)	80 (2032)
SEL100H	100 (2540)	49 (1245)	87 (2210)
SEL110H	110 (2794)	54 (1372)	96 (2438)

Standard Case: Height 8.25" (210mm) Depth 6" (152)

Sizes and specifications are subject to change at anytime.

Stewart
Filmscreen Corporation®
Picture Perfect

Headquarters: 1161 West Sepulveda Boulevard • Torrance, California 90502-2797 • (310) 784-5300 • (800) 762-4999 Fax: (310) 326-6870

Ohio: 3919 Bach-Buxton Road • Amelia, OH 45102 • (513) 753-0800 • Fax: (513) 753-0854

Europe: Vestre Gade 6E • 2605 Broendby • Denmark • +45 36-482204 Fax: +45 36-482299

Asia: No 53, Ubi Avenue 1 #01-43 Paya Ubi Industrial Park • Singapore 408934 • +65 67470555 Fax: +65 67472221

www.stewartfilm.com

comments@stewartfilm.com

V1.12.203