



## PLC-XW60

- Smallest and lightest LCD projector\*
- 2.000 ANSI-Lumen and XGA resolution provide a bright and detail-oriented projection
- Wide angle lens with 1,2 optical zoom allows flexible positioning (1.33–1.62 : 1)
- Automatic set-up (source recognition, keystone-correction and PC-adaption) enables operation within seconds
- Key lock function, pin code lock for security
- Direct Power On/Off lets you switch the projector on/off without delay
- Remote Control Code for increased user friendliness
- 5 years warranty, 1 year lamp warranty

\* Status March 11, 2008; category: LCD projectors with XGA resolution

## PLC-XW60

TECHNICAL DATA	PLC-XW60
Category	Business & Education
Panel	3 x 0.63" TFT p-Si (4 : 3), micro lens
Projection Lamp	165 W UHP (LMP-123)
Brightness in ANSI lumens	2,000
Lamp Life	3,500 h (eco mode)/2,000 h (normal mode)
Fan Noise	30 dB (eco mode)/34 dB (normal mode)
Standard Lens	F = 1.77–1.99/f = 17.4–21.1 mm*
Throw Distance Ratio	1.33–1.62 : 1*
Throw Distance	1.1–10.0 m*
Contrast Ratio	600 : 1
Resolution in Pixels	1,024 x 768 (XGA)
Image size min–max (diagonal)	40"–300"
Uniformity	85 %
Bandwidth/Frequency	110 MHz, horizontal 15–100 kHz, vertical 50–100 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL/M/N
Connections	Input 1: D-Sub15 (RGB) Input 2: D-Sub15 (RGB) or monitor out Input 3: RCA (Composite) Audio: 3.5 mm Stereo Jack for computer, 2 x RCA (R/L mono) for video Control input Jack: Mini DIN 8-pin (RS232 compatible)
Audio Function	1 W Mono
Keystone Correction	vertical +/-20°
Up/Down-Ratio	6 : 1 (Fixed U/D Ratio)
HDTV Compatibility	480i/480p/575i/575p/720p/1,035i/1,080i
Computer Compatibility	UXGA/SXGA/SXGA+/WXGA/XGA/SVGA/VGA/Mac
Zoom/Focus	1.2 x/manual
Power Consumption/Voltage	188 W (eco mode)/219 W (normal mode)/3,8 W (stand-by mode)/100–240 V
Warranty	5 years, 1 year lamp (max. 2,000 h)
Dimensions (W x H x D)	265 x 74 x 189 mm
Weight	1.6 kg
Standard Accessories	Remote control, batteries, user manual (CD-ROM), power cable, PIN code label, carrier bag, lens cover with fastener and cord
Optional Accessories	SCART/D-Sub 15 cable (POA-CA-SCART), remote control with laser pointer (POA-RCKIT03), components/D-Sub15 cable (POA-CA-COMPVA), presentation kit including mouse function (POA-RCKIT04), ceiling mounts: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)
Lenses	Standard Lens

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 07/2008

